




**Girella con dado in ottone o acciaio inox e raccordo maschio e guarnizione piatta in EPDM**  
**Adaptor union with male thread, brass/stainless steel nut and EPDM flat seal**  
**Übergangsverschraubung A.G. mit EPDM-Flachdichtung und Messing-oder Inoxmutter**




| Code      | d - R               | Dado   Nut<br>Überwurf.    | L                                    | Z  |  | MOQ |
|-----------|---------------------|----------------------------|--------------------------------------|----|---|-----|
| S64PC-LBP | 15-R $\frac{1}{2}$  | Ottone<br>Brass<br>Messing | 77                                   | 56 | 150   | 15  |
| S64QC-LBP | 15-R $\frac{3}{4}$  |                            | 80                                   | 59 | 180   | 15  |
| S64PD-LBP | 18-R $\frac{1}{2}$  |                            | 63                                   | 42 | 135   | 15  |
| S64QD-LBP | 18-R $\frac{3}{4}$  |                            | 66                                   | 45 | 160   | 15  |
| S64PE-LBP | 22-R $\frac{1}{2}$  |                            | 67                                   | 44 | 240   | 15  |
| S64QE-LBP | 22-R $\frac{3}{4}$  |                            | 69                                   | 46 | 220   | 15  |
| S64RE-LBP | 22-R1               |                            | 73                                   | 50 | 280   | 15  |
| S64RF-LBP | 28-R1               |                            | 78                                   | 54 | 400   | 15  |
| S64SG-LBP | 35-R1 $\frac{1}{4}$ |                            | 85                                   | 59 | 540   | 15  |
| S64TH-LBP | 42-R1 $\frac{1}{2}$ |                            | 90                                   | 58 | 630   | 15  |
| S64VJ-LBP | 54-R2               |                            | 104                                  | 67 | 1.060   | 15  |
| S65PC-LBP | 15-R $\frac{1}{2}$  |                            | Inox<br>Stainless steel<br>Edelstahl | 77 | 56  | 165 |
| S65QC-LBP | 15-R $\frac{3}{4}$  | 80                         |                                      | 59 | 190   | 15  |
| S65PD-LBP | 18-R $\frac{1}{2}$  | 63                         |                                      | 42 | 150   | 15  |
| S65QD-LBP | 18-R $\frac{3}{4}$  | 66                         |                                      | 45 | 175   | 15  |
| S65PE-LBP | 22-R $\frac{1}{2}$  | 67                         |                                      | 44 | 250   | 15  |
| S65QE-LBP | 22-R $\frac{3}{4}$  | 69                         |                                      | 46 | 230   | 15  |
| S65RE-LBP | 22-R1               | 73                         |                                      | 50 | 290   | 15  |
| S65RF-LBP | 28-R1               | 78                         |                                      | 54 | 390   | 15  |
| S65SG-LBP | 35-R1 $\frac{1}{4}$ | 85                         |                                      | 59 | 540   | 15  |
| S65TH-LBP | 42-R1 $\frac{1}{2}$ | 90                         |                                      | 58 | 610   | 15  |
| S65VJ-LBP | 54-R2               | 104                        |                                      | 67 | 1.010   | 15  |



**Doppio raccordo con dado in ottone o acciaio inox e guarnizione piatta in EPDM**  
**Straight union with press fittings on both ends, swivel nut in brass/st. steel and EPDM flat seal**  
**Doppelanschlussverschraubung mit EPDM-Flachdichtung und Messing- oder Inoxmutter**



| Code      | d - G               | Dado   Nut<br>Überwurf.              | L   | Z    |  | MOQ |
|-----------|---------------------|--------------------------------------|-----|------|---|-----|
| S66QC-LBP | 15-G $\frac{3}{4}$  | Ottone<br>Brass<br>Messing           | 99  | 57   | 176   | 15  |
| S66QD-LBP | 18-G $\frac{3}{4}$  |                                      | 86  | 44   | 154   | 15  |
| S66RE-LBP | 22-G1               |                                      | 94  | 48   | 247   | 15  |
| S66SF-LBP | 28-G1 $\frac{1}{4}$ |                                      | 100 | 52   | 358   | 15  |
| S66TG-LBP | 35-G1 $\frac{1}{2}$ |                                      | 110 | 57   | 579   | 15  |
| S66UH-LBP | 42-G1 $\frac{3}{4}$ |                                      | 119 | 55   | 655   | 15  |
| S66WJ-LBP | 54-G2 $\frac{1}{2}$ | 128                                  | 54  | 1001 | 15  |     |
| S68QC-LBP | 15-G $\frac{3}{4}$  | Inox<br>Stainless steel<br>Edelstahl | 99  | 57   | 189   | 15  |
| S68QD-LBP | 18-G $\frac{3}{4}$  |                                      | 86  | 44   | 168   | 15  |
| S68RE-LBP | 22-G1               |                                      | 94  | 48   | 245   | 15  |
| S68SF-LBP | 28-G1 $\frac{1}{4}$ |                                      | 100 | 52   | 374   | 15  |
| S68TG-LBP | 35-G1 $\frac{1}{2}$ |                                      | 110 | 57   | 574   | 15  |
| S68UH-LBP | 42-G1 $\frac{3}{4}$ |                                      | 119 | 55   | 635   | 15  |
| S68WJ-LBP | 54-G2 $\frac{1}{2}$ | 128                                  | 54  | 955  | 15  |     |