

## Safety data sheet according to UK REACH

Printing date 07.04.2025

Version: 7.01 (replaces version 7.00)

Revision: 17.07.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Trade name:** SONAX Cockpit Spray

**Article number:**

03433000

**UFI:** XJM5-500E-900A-NE8E

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Application of the substance / the mixture

Car care product

Detergents

Consumer uses: Private households / general public / consumers

Professional uses

**Uses advised against** There is currently no information available on this.

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

##### Further information obtainable from:

Product safety

E-mail: [erp@sonax.de](mailto:erp@sonax.de)

Phone: + +49 (0) 8431 53 217

##### United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: [info@aaoil.co.uk](mailto:info@aaoil.co.uk)

#### 1.4 Emergency telephone number:

**European Union:** +49 (0) 89 19240 (Poison Centre Munich)

**United Kingdom:** 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Carc. 1B H350 May cause cancer.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

##### Hazard pictograms



GHS02 GHS08

##### Signal word Danger

##### Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H350 May cause cancer.

##### Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

(Contd. on page 2)

GB

## Safety data sheet according to UK REACH

Printing date 07.04.2025

Version: 7.01 (replaces version 7.00)

Revision: 17.07.2024

**Trade name: SONAX Cockpit Spray**

(Contd. of page 1)

- P251 Do not pierce or burn, even after use.  
 P260 Do not breathe spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P308+P313 IF exposed or concerned: Get medical advice/attention.  
 P405 Store locked up.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH208 Contains Linalool. May produce an allergic reaction.

Buildup of explosive mixtures possible without sufficient ventilation.

**2.3 Other hazards****Results of PBT and vPvB assessment****PBT:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

**vPvB:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

**Determination of endocrine-disrupting properties**

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

**3.2 Mixtures****Description:** Formulation consisting of pressurised gas and solvents with additives**Dangerous components:**

CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	20-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	20-<25%
EC No 934-956-3 Reg.nr.: 01-2119827000-58-xxxx	Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics Alternative CAS number: 64742-46-7 ⚠ Asp. Tox. 1, H304	15-<20%
EC No 934-954-2 Reg.nr.: 01-2119826592-36-xxxx	Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics Alternative CAS number: 64742-46-7 ⚠ Asp. Tox. 1, H304	10-<15%
EINECS: 265-149-8 Reg.nr.: 01-2119453414-43-xxxx	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics Alternative CAS number: 64742-47-8 ⚠ Asp. Tox. 1, H304, EUH066	10-<15%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 78-70-6 EINECS: 201-134-4 Reg.nr.: 01-2119474016-42-xxxx	linalool ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317	<0.25%

**Regulation (EC) No 648/2004 on detergents / Labelling for contents**

aliphatic hydrocarbons	≥30%
perfumes (LINALOOL, GERANIOL, LINALYL ACETATE, CAMPHOR, CITRAL, LIMONENE, CITRONELLOL, CARVONE)	

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)

## Safety data sheet according to UK REACH

Printing date 07.04.2025

Version: 7.01 (replaces version 7.00)

Revision: 17.07.2024

Trade name: SONAX Cockpit Spray

(Contd. of page 2)

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### General information:

Take affected persons out into the fresh air.

Remove soiled clothing

##### After inhalation:

Supply fresh air.

In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.

##### After skin contact:

Wash the areas of skin affected with water and a mild detergent.

If skin irritation continues, consult a doctor.

##### After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

Headache

Dizziness

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing agents:

Foam

Carbon dioxide

Fire-extinguishing powder

Water haze

For safety reasons unsuitable extinguishing agents: Water with full jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO<sub>2</sub>)

Nitrogen oxides (NO<sub>x</sub>)

#### 5.3 Advice for firefighters

##### Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

##### Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

##### For non-emergency personnel

Keep away from ignition sources.

Particular danger of slipping on leaked/spilled product.

For emergency responders Wear protective equipment. Keep unprotected persons away.

#### 6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

#### 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

## Safety data sheet according to UK REACH

Printing date 07.04.2025

Version: 7.01 (replaces version 7.00)

Revision: 17.07.2024

Trade name: SONAX Cockpit Spray

(Contd. of page 3)

Dispose contaminated material as waste according to section 13.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

**7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Buildup of explosive mixtures possible without sufficient ventilation.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Highly volatile, flammable constituents are released during processing.

Protect against electrostatic charges.

**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:**

Provide solvent resistant, sealed floor.

Observe official regulations on storing packagings with pressurised containers.

**Information about storage in one common storage facility:**

Store away from foodstuffs.

Observe local/state/federal regulations.

**Further information about storage conditions:**

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from heat and direct sunlight.

Recommended storage temperature: 20 °C.

**7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

**8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****CAS: 106-97-8 butane**

WEL (Great Britain)	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm
	Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)

OEL (Ireland)	Short-term value: 1000 ppm
---------------	----------------------------

**CAS: 74-98-6 propane**

OEL (Ireland)	Asphx
---------------	-------

**CAS: 75-28-5 isobutane**

OEL (Ireland)	Short-term value: 1000 ppm
---------------	----------------------------

**Regulatory information**

WEL (Great Britain): EH40/2020

OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work

**Additional information:** The lists valid during the making were used as basis.

(Contd. on page 5)

GB

## Safety data sheet according to UK REACH

Printing date 07.04.2025

Version: 7.01 (replaces version 7.00)

Revision: 17.07.2024

Trade name: SONAX Cockpit Spray

(Contd. of page 4)

### 8.2 Exposure controls

#### Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

#### Individual protection measures, such as personal protective equipment

##### General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

##### Respiratory protection:

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

**Hand protection** Not required in normal cases.

**Eye/face protection** Not required in normal cases

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

##### Physical state

Fluid

##### Colour:

Light yellow

##### Odour:

Citrus

##### Melting point/freezing point:

Undetermined.

##### Boiling point or initial boiling point and boiling range

Not applicable, as aerosol.

##### Flammability

Extremely flammable aerosol.

##### Lower and upper explosion limit

##### Lower:

1.5 Vol % (CAS: 106-97-8 butane)

##### Upper:

10.9 Vol % (CAS: 74-98-6 propane)

##### Flash point:

Not applicable, as aerosol.

##### Decomposition temperature:

Not determined.

##### pH

Not applicable.

##### Viscosity:

##### Kinematic viscosity at 40 °C

<20.5 mm<sup>2</sup>/s  
(Active ingredient data )

##### Solubility

##### water:

Not miscible or difficult to mix.

##### Partition coefficient n-octanol/water (log value)

Not determined.

##### Vapour pressure:

Not determined.

##### Density and/or relative density

##### Density at 20 °C:

0.81-0.83 g/cm<sup>3</sup>

##### Vapour density

Not determined.

### 9.2 Other information

#### Appearance:

##### Form:

Aerosol

#### Important information on protection of health and environment, and on safety.

##### Ignition temperature:

Not determined.

##### Explosive properties:

In use, may form flammable/explosive vapour-air mixture.

#### Change in condition

##### Evaporation rate

Not applicable.

#### Information with regard to physical hazard classes

##### Explosives

Void

##### Flammable gases

Void

(Contd. on page 6)

## Safety data sheet according to UK REACH

Printing date 07.04.2025

Version: 7.01 (replaces version 7.00)

Revision: 17.07.2024

Trade name: SONAX Cockpit Spray

(Contd. of page 5)

**Aerosols**

Extremely flammable aerosol.

Pressurised container: May burst if heated.

**Oxidising gases** Void**Gases under pressure** Void**Flammable liquids** Void**Flammable solids** Void**Self-reactive substances and mixtures** Void**Pyrophoric liquids** Void**Pyrophoric solids** Void**Self-heating substances and mixtures** Void**Substances and mixtures, which emit flammable****gases in contact with water** Void**Oxidising liquids** Void**Oxidising solids** Void**Organic peroxides** Void**Corrosive to metals** Void**Desensitised explosives** Void**SECTION 10: Stability and reactivity****10.1 Reactivity** No dangerous reactions known.**10.2 Chemical stability** Stable under normal conditions.**10.3 Possibility of hazardous reactions** Develops readily flammable gases/fumes.**10.4 Conditions to avoid**

An increase in pressure may lead to bursting.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

**10.5 Incompatible materials:** strong oxidizing agents**10.6 Hazardous decomposition products:** No dangerous decomposition products known.**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity** Based on available data, the classification criteria are not met.**LD/LC50 values relevant for classification:****Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics**

Oral LD50 &gt;5,000 mg/kg (rat) (OECD 401)

Dermal LD50 &gt;3,160 mg/kg (rabbit) (OECD 402)

Inhalative LC50 / 4h >5.266 mg/m<sup>3</sup> (rat) (OECD 403)**Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics**

Oral LD50 &gt;5,000 mg/kg (rat) (OECD 401)

Dermal LD50 &gt;3,160 mg/kg (rabbit) (OECD 402)

Inhalative LC50 / 4h >5.266 mg/m<sup>3</sup> (rat) (OECD 403)**Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics**

Oral LD50 &gt;5,000 mg/kg (rat) (OECD 401)

Dermal LD50 &gt;5,000 mg/kg (rabbit) (OECD 402)

Inhalative LC50 / 4h >5.6 mg/m<sup>3</sup> (rat) (OECD 403)**CAS: 78-70-6 linalool**

Oral LD50 2,790 mg/kg (rat)

Dermal LD50 5,610 mg/kg (rabbit)

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

(Contd. on page 7)



## Safety data sheet according to UK REACH

Printing date 07.04.2025

Version: 7.01 (replaces version 7.00)

Revision: 17.07.2024

Trade name: SONAX Cockpit Spray

(Contd. of page 6)

**Serious eye damage/irritation** Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation**

Contains Linalool. May produce an allergic reaction.

Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity**

May cause cancer.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT-single exposure** Based on available data, the classification criteria are not met.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

**11.2 Information on other hazards**

**Endocrine disrupting properties**

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

## SECTION 12: Ecological information

**12.1 Toxicity** There are no ecotoxicological data available on this mixture.

**Aquatic toxicity:**

**CAS: 106-97-8 butane**

LC50 / 96 h 27.98 mg/l (fish)

EC50 / 4 d 7.71 mg/l (algae)

**CAS: 74-98-6 propane**

LC50 / 96 h 27.98 mg/l (fish)

EC50 / 96 h 7.71 mg/l (algae)

**Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics**

LC50 / 4 d >1,028 mg/l (*Scophtalamus maximus*) (OECD 203)

LC50 / 48h >3,193 mg/l (*Acartia tonsa*)

NOEC / 21 d >1,000 mg/l (*Daphnia magna*)

NOEC / 28d >1,000 mg/l (*Oncorhynchus mykiss*)

LC50 / 3 d >10,000 mg/l (*Skeletonema costatum*)

**Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics**

LC50 / 2 d >3,193 mg/l (*Acartia tonsa*)

LC50 / 4 d >1,028 mg/l (*Scophtalamus maximus*) (OECD 203)

NOEC / 21 d >1,000 mg/l (*Daphnia magna*)

NOEC / 28d >1,000 mg/l (*Oncorhynchus mykiss*)

EC50 / 3 d >10,000 mg/l (*Skeletonema costatum*)

**Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics**

LC50 / 2 d >1,000 mg/l (*Daphnia magna*) (OECD 202)

LC50 / 4 d >1,000 mg/l (*Oncorhynchus mykiss*) (OECD 203)

NOEC / 21 d >1,000 mg/l (*Daphnia magna*)

NOEC / 28d >1,000 mg/l (*Oncorhynchus mykiss*)

EC50 / 3 d >1,000 mg/l (*Pseudokirchneriella subcapitata*) (OECD 201)

**CAS: 75-28-5 isobutane**

LC50 / 96 h 27.98 mg/l (fish)

EC50 / 4 d 7.71 mg/l (algae)

**12.2 Persistence and degradability**

**Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics**

Biodegradation 74 %

(Contd. on page 8)

## Safety data sheet according to UK REACH

Printing date 07.04.2025

Version: 7.01 (replaces version 7.00)

Revision: 17.07.2024

Trade name: SONAX Cockpit Spray

(Contd. of page 7)

**Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics**

Biodegradation 74 %

**Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics**

Biodegradation 67.6 %

**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**12.5 Results of PBT and vPvB assessment****PBT:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

**vPvB:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB

**12.6 Endocrine disrupting properties**

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

**12.7 Other adverse effects****Additional ecological information:****General notes:** The product may not be released into the environment without control.

### SECTION 13: Disposal considerations

**13.1 Waste treatment methods****Recommendation** Waste must be disposed of while observing the local, official regulations.**European waste catalogue**

Disposal / product + Disposal / contaminated packaging

15 01 10\* packaging containing residues of or contaminated by dangerous substances

**Uncleaned packaging:****Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

**14.1 UN number or ID number**

ADR/RID/ADN, IMDG, IATA UN1950

**14.2 UN proper shipping name**

ADR/RID/ADN	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable

**14.3 Transport hazard class(es)**

ADR/RID/ADN



<b>Class</b>	2 5F Gases.
<b>Label</b>	2.1

IMDG, IATA



<b>Class</b>	2.1 Gases.
<b>Label</b>	2.1

(Contd. on page 9)



## Safety data sheet according to UK REACH

Printing date 07.04.2025

Version: 7.01 (replaces version 7.00)

Revision: 17.07.2024

Trade name: SONAX Cockpit Spray

(Contd. of page 8)

**14.4 Packing group**

ADR/RID/ADN, IMDG, IATA      Void

**14.5 Environmental hazards:**

Marine pollutant:      No

**14.6 Special precautions for user** Warning: Gases.**Transport/Additional information:****ADR/RID/ADN**

Limited quantities (LQ)      1L

Transport category      2

Tunnel restriction code      D

**UN "Model Regulation":**      UN1950, AEROSOLS, 2.1**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
**European Directives:**

Directive 2010/75/EU (VOC) 50.33 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) P3a FLAMMABLE AEROSOLS

REGULATION (EU) 2019/1148

**Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

**Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

**National regulations:****Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

**Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

**Relevant phrases**

H220      Extremely flammable gas.

H280      Contains gas under pressure; may explode if heated.

H304      May be fatal if swallowed and enters airways.

H315      Causes skin irritation.

H317      May cause an allergic skin reaction.

H319      Causes serious eye irritation.

EUH066 Repeated exposure may cause skin dryness or cracking.

**Classification according to Regulation (EC) No 1272/2008**

Aerosols, Section 2.3.1      On basis of test data

Carcinogenicity	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
-----------------	--

**Date of previous version:** 22.02.2024**Version number of previous version:** 7.00**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 10)

## Safety data sheet according to UK REACH

Printing date 07.04.2025

Version: 7.01 (replaces version 7.00)

Revision: 17.07.2024

**Trade name: SONAX Cockpit Spray**

(Contd. of page 9)

NOEL = No Observed Effect Level  
 NOEC = No Observed Effect Concentration  
 LC = Lethal Concentration  
 EC50 = half maximal effective concentration  
 log POW = Octanol / water partition coefficient  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 ATE: acute toxicity estimate  
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 IOELV = indicative occupational exposure limit values  
 Flam. Gas 1A: Flammable gases – Category 1A  
 Aerosol 1: Aerosols – Category 1  
   : Aerosols – Category 3  
 Press. Gas (Comp.): Gases under pressure – Compressed gas  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Skin Sens. 1B: Skin sensitisation – Category 1B  
 Carc. 1B: Carcinogenicity – Category 1B  
 Asp. Tox. 1: Aspiration hazard – Category 1

**\* Data compared to the previous version altered.**

GB