EURO-LOCK

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.05.2018

*

*

Version number 17

Revision: 30.05.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking
· 1.1 Product identifier
· Trade name: Rost-Protector-Spezial
 Article number: LOS115 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. Application of the substance / the mixture Lubricant
 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: Euro-Lock Vertriebs-GmbH Nordweststr. 3 D - 59387 Ascheberg Tel.: +49 (0) 2593/95887-0 Fax: +49 (0) 2593/95887-29 www.euro-lock.de info@euro-lock.de Further information obtainable from: Tel.: +49 (0) 2593/95887-0 info@euro-lock.de 1.4 Emergency telephone number: Tel.: +49 (0) 2593/95887-0 Monday - Thursday 8.00 a.m 5.00 p.m. and Friday 8.00 a.m 1.00 p.m.
SECTION 2: Hazards identification
 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008
GHS02 flame
\checkmark
Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
GHS07
Eye Irrit. 2H319Causes serious eye irritation.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
 • 2.2 Label elements • Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. • Hazard pictograms
GHS02 GHS07
· Signal word Danger
 Hazard-determining components of labelling: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics White mineral oil, petroleum Hazard statements
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319 Causes serious eye irritation. • Precautionary statements
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children. (Contd. on page 2)

٦

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.05.2018

Г

EURO-LOCK

Version number 17

Revision: 30.05.2018

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P280 Wear protective gloves / eye protection / face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i present and easy to do. Continue rinsing. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 Dispose of contents/container to hazardous or special waste collection point. • Additional information: EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation. • 2.3 Other hazards		(Contd. of page 1)
P251 Do not pierce or burn, even after use. P280 Wear protective gloves / eye protection / face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i present and easy to do. Continue rinsing. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 Dispose of contents/container to hazardous or special waste collection point. Additional information: EUH066 Repeated exposure may cause skin dryness or cracking.	P210	
P280 Wear protective gloves / eye protection / face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i present and easy to do. Continue rinsing. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 Dispose of contents/container to hazardous or special waste collection point. • Additional information: EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation.	P211	Do not spray on an open flame or other ignition source.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i present and easy to do. Continue rinsing. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 Dispose of contents/container to hazardous or special waste collection point. Additional information: EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation. 	P251	Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 Dispose of contents/container to hazardous or special waste collection point. • Additional information: EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation.	P280	Wear protective gloves / eye protection / face protection.
 P501 Dispose of contents/container to hazardous or special waste collection point. Additional information: EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation. 	P305+P351+P3	
 Additional information: EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation. 	P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation.	P501	Dispose of contents/container to hazardous or special waste collection point.
Buildup of explosive mixtures possible without sufficient ventilation.	· Additional inf	ormation:
	EUH066 Repea	ated exposure may cause skin dryness or cracking.
· 2.3 Other hazards	Buildup of exp	losive mixtures possible without sufficient ventilation.
	· 2.3 Other haza	ards
	· PBT: Not appl	icable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EC number: 918-481-9 Reg.nr.: 01-2119457273-39-xxxx	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics	25-<50%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1, H220; Press. Gas (Comp.), H280	20-<25%
CAS: 8042-47-5 EINECS: 232-455-8 Reg.nr.: 01-2119487078-27-xxxx	White mineral oil, petroleum Å Asp. Tox. 1, H304	20-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<20%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-<5%
CAS: 110-25-8 EINECS: 203-749-3	oleoylsarcosine Eye Dam. 1, H318; Aquatic Acute 1, H400; Acute Tox. 4, H332; Skin Irrit. 2, H315	1-<2.5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly. Immediately remove any clothing soiled by the product.

(Contd. on page 3)

Version number 17

Revision: 30.05.2018

Trade name: Rost-Protector-Spezial

Article-number: LOS115

(Contd. of page 2)

· After eye contact:

EURO-LOCK

Printing date 30.05.2018

- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Do not induce vomiting; call for medical help immediately.
- \cdot 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- Foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- \cdot 5.2 Special hazards arising from the substance or mixture
- Can form explosive gas-air mixtures. Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

- · 5.3 Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.
- · Additional information
- Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 Ensure adequate ventilation Keep away from ignition sources.
- 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- 6.4 Reference to other sections See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Avoid contact with skin and eyes.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)

Printing date 30.05.2018

EURO-LOCK

Version number 17

Revision: 30.05.2018

```
Trade name: Rost-Protector-Spezial
```

Article-number: LOS115

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

· Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Protect from heat and direct sunlight.

· 7.3 Specific end use(s) Industrial processing

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

• Ingredients with limit values that require monitoring at the workplace:

CAS: 106-97-8 butane WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- Respiratory protection: Not necessary if room is well-ventilated.
- · Recommended filter device for short term use: Filter AX
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- Material of gloves
- Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.45 mm

- \cdot Penetration time of glove material
- ≥240 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Tightly sealed goggles

· Body protection: Protective work clothing

9.1 Information on basic 1	physical and chemical properties	
General Information	,	
Appearance:		
Form:	Aerosol	
Colour:	Colourless	
Odour:	Solvent-like	





Printing date 30.05.2018

Version number 17

Revision: 30.05.2018

Trade name: Rost-Protector-Spezial

Article-number: LOS115

	(Contd. of pa
· Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. Not applicable, as aerosol.
Flash point:	Not applicable, as aerosol.
Flammability (solid, gas):	Not applicable.
Ignition temperature:	>200 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Explosive properties:	Not determined.
Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapour pressure:	Not determined.
Density at 20 °C: Relative density Vapour density Evaporation rate	0.68451 g/cm ³ Not determined. Not determined. Not applicable.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity: Dynamic: Kinematic: Organic solvents: VOC (EC)	Not determined. Not determined. 76.1 % 521.1 g/l
Solids content: • 9.2 Other information	0.0 % No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Aldehyde

Carbon monoxide and carbon dioxide

(Contd. on page 6)



Printing date 30.05.2018

Version number 17

Revision: 30.05.2018

Trade name: Rost-Protector-Spezial

Article-number: LOS115

(Contd. of page 5)

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative LC50/4 h 558 mg/l

CAS: 110-25-8 oleoylsarcosine

Inhalative LC50/4 h 11 mg/l (ATE)

· Primary irritant effect:

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- **Remark:** Harmful to fish
- · Additional ecological information:
- · General notes:
- Harmful to aquatic organisms

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

16 05 04*	gases in pressure containers (including halons) containing hazardous substances		
15 01 04	metallic packaging		
		(0	. 1





Printing date 30.05.2018

Version number 17

Revision: 30.05.2018

Trade name: Rost-Protector-Spezial

Article-number: LOS115

(Contd. of page 6)

· Uncleaned packaging:

*

• **Recommendation:** Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR/RID/ADN, IMDG, IATA	UN1950
 · 14.2 UN proper shipping name · ADR/RID/ADN · IMDG · IATA 	UN1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR/RID/ADN	
· Class	2 5F Gases.
· Label	2.1
Close	2.1
· Class · Label	2.1 2.1
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
• 14.6 Special precautions for user • Danger code (Kemler):	Warning: Gases.
· EMS Number:	F-D,S-U
 Stowage Code Segregation Code 	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity abo 1 litre: Category B. For WASTE AEROSOLS: Catego C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of
	litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with capacity above 1 litre: Segregation as for the appropria subdivision of class 2. For WASTE AEROSOL Segregation as for the appropriate subdivision of class 2
· 14.7 Transport in bulk according to An Marpol and the IBC Code	nex II of Not applicable.



Printing date 30.05.2018

Version number 17

Revision: 30.05.2018

Trade name: Rost-Protector-Spezial

Article-number: LOS115

d. of page 7

SECTION 15: Regulatory information

 \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements $150\ t$
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements $500\ t$
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H400 Very toxic to aquatic life.
- · Department issuing SDS: Product Safety department.
- · Contact: info@euro-lock.de
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent

(Contd. on page 9)



Printing date 30.05.2018

Version number 17

Revision: 30.05.2018

Trade name: Rost-Protector-Spezial

Article-number: LOS115

(Contd. of page 8)

GB

PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1: Flammable gases – Category 1
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
* **Data compared to the previous version altered.**